




# Beghelli

## LUCE

---

### BS101 LED-ECO

## ■ ■ ■ features + benefits

<p><b>HIGH PERFORMANCE</b></p>	<ul style="list-style-type: none"> <li>• Increased lumen output while decreasing overall consumption.</li> <li>• From 5999 up to 6615 lm with just one LED board.</li> <li>• 55W</li> </ul>
<p><b>DIFFUSER</b></p>	<ul style="list-style-type: none"> <li>• UV stabilized polycarbonate frosted lens reduces glare.</li> <li>• Provides a clean light distribution without any striations.</li> </ul>
<p><b>IP65 PROTECTION</b></p>	<ul style="list-style-type: none"> <li>• For installation in dust filled environments.</li> <li>• Protected against low pressure jets of water from all directions</li> </ul>
<p><b>LIGHT WEIGHT DESIGN</b></p>	<ul style="list-style-type: none"> <li>• 9lbs, tool-less easy to install.</li> <li>• 4ft long.</li> </ul>
<p><b>DIMMING</b></p>	<ul style="list-style-type: none"> <li>• 0-10V standard, compatible with most dimming devices.</li> </ul>
<p><b>DIFFERENT MOUNTING SYSTEMS</b></p>	<ul style="list-style-type: none"> <li>• Surface mount standard, aviation cable (AC), single &amp; double pendants (SPK, DPK), chain hang (CH), trunion mount (TM), swivel double pendant kit (SVLDPK), and pivot mount (PM).</li> </ul>
<p><b>EXPECTED LED LIFE</b></p>	<ul style="list-style-type: none"> <li>• L70 rated &gt;60,000.</li> </ul>
<p><b>COLOR TEMPERATURE</b></p>	<ul style="list-style-type: none"> <li>• 3500K, 4000K and 5000K standard.</li> <li>• &gt;80 CRI</li> </ul>