



BS100LED-2PLUS

■ ■ ■ features + benefits

<p>HIGH PERFORMANCE</p>	<ul style="list-style-type: none"> • Increased lumen output while decreasing overall consumption. • LO: 5518 up to 6069 lm and HO: 7546 up to 8299 lm. • 50W (LO) and 70W (HO) versions offered.
<p>DIFFUSER</p>	<ul style="list-style-type: none"> • UV stabilized polycarbonate frosted lens reduces glare. • Provides a clean light distribution without any striations.
<p>IP66 PROTECTION</p>	<ul style="list-style-type: none"> • For installation in wet location and dust filled environments. • Suitable for wash-down areas with high psi.
<p>LIGHT WEIGHT DESIGN</p>	<ul style="list-style-type: none"> • Just 5lbs, tool-less easy to install. • 2ft long.
<p>DIMMING</p>	<ul style="list-style-type: none"> • 0-10V standard, compatible with most dimming devices.
<p>DIFFERENT MOUNTING SYSTEMS</p>	<ul style="list-style-type: none"> • Surface mount standard, aviation cable (AC), single & double pendants (SPK, DPK), chain hang (CH), trunnion mount TM, direct mount (DM), magnetic mount (MM) and pivot mount (PM).
<p>EXPECTED LED LIFE</p>	<ul style="list-style-type: none"> • L70 rated >60,000.
<p>COLOR TEMPERATURE</p>	<ul style="list-style-type: none"> • 3500K, 4000K and 5000K standard. • >80 CRI