

## 









24ga rolled steel, high pressure static powder coating	Added durability for installations in special environments
High performance optics	<ul> <li>Micro-prismatic light distribution provides glare control and optimal performance</li> <li>Reduce the number of fixtures to be maintained in an area</li> </ul>
Tempered glass lens	<ul><li>Has an IK09 (impact resistant) rating</li><li>Will not turn yellow over time, even in higher temperatures</li></ul>
72" line cord	<ul> <li>Installation time is approximately 50% less than comparable products</li> <li>Reduced labor time = money saved</li> </ul>
Single entry point	<ul> <li>Maintains the integrity of the luminaire</li> <li>Eliminates errors in installation and maintenance</li> </ul>
IP66 protection	<ul> <li>For installation in wet locations and dust filled environments</li> <li>Suitable for high pressure wash down areas (1450 psi)</li> </ul>
Nema 4X Rated	<ul> <li>Approved for outdoor use</li> <li>Protected against ingress of solid foreign objects (windblown dust) and respect to harmful effects on the equipment due to the ingress of water (rain, sleet, snow, splashing water, and hose directed water)</li> </ul>
Sanitation Listed	Meets the rigorous sanitation, electrical safety and performance standards for food safe applications.
Logica (Controls Solution)	External occupancy sensors

Warranty • 7-year warranty

