



BX950

Features

Benefits

| | |
|---|---|
| <ul style="list-style-type: none"> • Zinc dipped, 24ga, Steel monocoque housing | <ul style="list-style-type: none"> • Added durability for installations in special environments |
| <ul style="list-style-type: none"> • Ships 100% lamped and includes a 72" line cord | <ul style="list-style-type: none"> • Installation time is approximately 50% less than competitor's comparable products • Reduced labor time = money saved |
| <ul style="list-style-type: none"> • Removable lamp & ballast tray with quick disconnect | <ul style="list-style-type: none"> • Improved safety with automatic disconnect, power is automatically disengaged • Maintenance is simplified with replaceable trays; maintenance can be done on the ground |
| <ul style="list-style-type: none"> • High performance optics | <ul style="list-style-type: none"> • Reduce the number of fixture to be installed in an area • Reduce the number of fixture to be maintained in an area |
| <ul style="list-style-type: none"> • Tempered glass lens | <ul style="list-style-type: none"> • Impact resistant • Will not turn yellow over time |
| <ul style="list-style-type: none"> • IP66 protection | <ul style="list-style-type: none"> • For installation in wet location and dust filled environments • Suitable for washdown areas with high psi |
| <ul style="list-style-type: none"> • Single entry point | <ul style="list-style-type: none"> • Maintain the integrity of the luminaire • Eliminate errors in installation and maintenance |



BX940



BX920 (4')



BX920 (2')



BX950