



CASTEX 300



... features + benefits

HAZARDOUS CLASSIFICATIONS	<ul style="list-style-type: none"> • Class I, Division 2, Groups A, B, C, D • Class II, Division 1, Groups E, F, G • Class II, Division 2, Groups F, G • Class III
PERFORMANCE RANGE	<ul style="list-style-type: none"> • VLO: 60W @ 8400 lm • LO: 100W @ 14000 lm • MO: 150W @ 21000 lm • HO: 200W @ 28000 lm
OPERATING TEMPERATURE	<ul style="list-style-type: none"> • -40°F to 131°F (-40°C to 55°C) • Allows for installation in harsh environments.
DURABLE CONSTRUCTION	<ul style="list-style-type: none"> • A383 aluminum alloy • Provides added durability for installations in corrosive environments.
DIFFUSER	<ul style="list-style-type: none"> • 4mm tempered glass for 120° distribution.
SERIOUS PROTECTION	<ul style="list-style-type: none"> • Rated IP66 making it suitable for installations in wet and dust filled locations.
MULTIPLE MOUNTING OPTIONS	<ul style="list-style-type: none"> • Hook Mount • Pendant Kit • Wall / Surface
WARRANTY	<ul style="list-style-type: none"> • 5 Years