



CASTEX 310



... features + benefits

HAZARDOUS CLASSIFICATIONS	<ul style="list-style-type: none">• Class I, Division 1, Groups C, D• Class I, Division 2, Groups A, B, C, D• Class II, Division 1, Groups E, F, G• Class II, Division 2, Groups F, G• Class III
PERFORMANCE RANGE	<ul style="list-style-type: none">• VLO: 60W @ 8400 lm• LO: 80W @ 11200 lm• MO: 100W @ 14000 lm• HO: 150W @ 21000 lm• VHO: 250W @ 35000 lm
OPERATING TEMPERATURE	<ul style="list-style-type: none">• -40°F to 140°F (-40°C to 60°C)• Allows for installation in harsh environments.
DURABLE CONSTRUCTION	<ul style="list-style-type: none">• A383 aluminum alloy• Provides added durability for installations in corrosive environments.
DIFFUSER	<ul style="list-style-type: none">• 4mm tempered glass for 120° distribution.
SERIOUS PROTECTION	<ul style="list-style-type: none">• Rated IP66 making it suitable for installations in wet and dust filled locations.
MULTIPLE MOUNTING OPTIONS	<ul style="list-style-type: none">• Hook Mount• Pendant Kit• Wall / Surface
WARRANTY	<ul style="list-style-type: none">• 5 Years