



CASTEX 700



... features + benefits

| | |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| HAZARDOUS CLASSIFICATIONS | <ul style="list-style-type: none">• Class I, Division 1, Groups C, D• Class I, Division 2, Groups A, B, C, D• Class II, Division 1, Groups E, F, G• Class II, Division 2, Groups F, G• Class III |
| COLOR OPTIONS | <ul style="list-style-type: none">• Red lettering• Green lettering |
| OPERATING TEMPERATURE | <ul style="list-style-type: none">• -40°F to 140°F (-40°C to 60°C)• Allows for installation in harsh environments. |
| DURABLE CONSTRUCTION | <ul style="list-style-type: none">• Die-cast copper free aluminum• Provides added durability for installations in corrosive environments. |
| OPERATION | <ul style="list-style-type: none">• SA (self-powered) |
| SERIOUS PROTECTION | <ul style="list-style-type: none">• Rated IP66 making it suitable for installations in wet and dust filled locations. |
| MULTIPLE MOUNTING OPTIONS | <ul style="list-style-type: none">• Pendant Kit• Wall / Surface |
| WARRANTY | <ul style="list-style-type: none">• 5 Years |