



Feature	Benefit
<ul style="list-style-type: none"> <li>3 different models</li> </ul>	<ul style="list-style-type: none"> <li>BS710LED: glass ring diffuser</li> <li>BS720LED: metal ring</li> <li>BS730LED: no ring</li> </ul>
<ul style="list-style-type: none"> <li>4 different distributions</li> </ul>	<ul style="list-style-type: none"> <li>Narrow 10°</li> <li>Medium 20°</li> <li>Wide 36°</li> <li>No optical lens &gt; 40°</li> </ul>
<ul style="list-style-type: none"> <li>Architectural lowbay</li> </ul>	<ul style="list-style-type: none"> <li>Ideal for cafes, retail, open ceiling environments, lofts, offices, restaurants and residential.</li> </ul>
<ul style="list-style-type: none"> <li>36W</li> </ul>	<ul style="list-style-type: none"> <li>Energy saving</li> </ul>
<ul style="list-style-type: none"> <li>2 piece design</li> </ul>	<ul style="list-style-type: none"> <li>Allows for easy installation and maintenance</li> </ul>
<ul style="list-style-type: none"> <li>Powered by Samsung</li> </ul>	<ul style="list-style-type: none"> <li>1821-2581 lumen range per comparison chart</li> <li>LM70 rated for 85,000 hours</li> </ul>
<ul style="list-style-type: none"> <li>Refractors &amp; Reflectors</li> </ul>	<ul style="list-style-type: none"> <li>12" and 16" acrylic refractors and aluminum reflectors are offered. Custom colors available</li> </ul>
<ul style="list-style-type: none"> <li>3 different color temperatures, single color and RGB</li> </ul>	<ul style="list-style-type: none"> <li>3500k, 4100k &amp; 5700k</li> <li>Red, amber, green, cyan, blue or royal blue (contact factory for custom colors)</li> </ul>



The DRACO is ideal for:

- cafes
- retail
- open ceiling
- lofts
- offices
- restaurants
- schools
- libraries
- residential



### ENERGY COMPARISON CHART

NOTE: 4100K shown below, for all energy comparison details see spec pages

LAMP	EFFICACY (lm/W)	CONSUMPTION WATTAGE	LUMEN OUTPUT	CRI	BEAM ANGLE	L70 (hrs.)
DRACO BS710-4100K-MEDIUM	62.15	35.13	2183	80+	17.8°	85,000
DRACO BS710-4100K-WIDE	63.32	34.90	2210	80+	22.2°	85,000
DRACO BS710-4100K-NARROW	69.31	35.06	2430	80+	12.5°	85,000
DRACO BS720-4100K-MEDIUM	60.49	33.49	2026	85+	26.2°	85,000
DRACO BS720-4100K-WIDE	61.22	33.47	2049	85+	33.9°	85,000
DRACO BS720-4100K-NARROW	72.65	33.38	2425	85+	13.6°	85,000
DRACO BS730-4100K-MEDIUM	65.88	34.6	2279.5	80+	21.6°	85,000
DRACO BS730-4100K-WIDE	69.32	34.64	2401.3	80+	31.2°	85,000
DRACO BS730-4100K-NARROW	70.97	34.54	2451	80+	11.1°	85,000