



HZ950

Features

Benefits

<ul style="list-style-type: none"> • Hazardous rating 	<ul style="list-style-type: none"> • Class I, Division 2, Class I, Zone 2 • Groups A, B, C & D
<ul style="list-style-type: none"> • Ideal applications 	<ul style="list-style-type: none"> • Bottling facilities, rendering plants, refineries, gasoline storage, dry cleaning plants, spray finishing areas, aircraft hangars and fuel servicing areas. • HZ/BX920S (stainless steel) - is ideal for food processing, refrigeration and cold storage.
<ul style="list-style-type: none"> • Available 304 stainless steel 22ga. housing 	<ul style="list-style-type: none"> • Available as HZ/BX920s - 4ft only • Comes standard with a clear safety film: 4mm clear safety film, modifies glass to safe breakage. Scratch, heat, impact and blast resistant. Complies with EN12600 Class 2.
<ul style="list-style-type: none"> • Zinc coated, 24ga. steel monocoque housing 	<ul style="list-style-type: none"> • Added durability for installations in special environments
<ul style="list-style-type: none"> • Ships 100% lamped and includes a 72" line cord 	<ul style="list-style-type: none"> • Installation time is reduced • Reduced labor time = money saved
<ul style="list-style-type: none"> • Removable lamp & ballast tray with quick disconnect 	<ul style="list-style-type: none"> • Improved safety with automatic disconnect, power is automatically disengaged • Maintenance is simplified with replaceable trays; maintenance can be done on the ground
<ul style="list-style-type: none"> • High performance optics 	<ul style="list-style-type: none"> • Reduce the number of luminaires to be installed or maintained in an area
<ul style="list-style-type: none"> • Tempered glass lens 	<ul style="list-style-type: none"> • Impact resistant • Will not turn yellow over time
<ul style="list-style-type: none"> • IP66 protection 	<ul style="list-style-type: none"> • For installation in wet location & dust filled environments • Suitable for wash down areas with high psi
<ul style="list-style-type: none"> • Single entry point 	<ul style="list-style-type: none"> • Maintain the integrity of the luminaire • Eliminate errors in installation and maintenance



HZ940



HZ920 (4')
HZ920S (4')



HZ920 (2')



HZ960