



## • • features + benefits

| PERFORMANCE       | <ul> <li>Up to 123lm/W.</li> <li>1500 - 33,000lm.</li> <li>15W, 30W, 50W, 80W, 100W, 140W, 240W and 280W versions offered.</li> </ul>   |
|-------------------|---|
| HOUSING           | <ul> <li>Die-cast aluminum housing.</li> <li>Durable powder coat dark bronze powder coat finish.</li> </ul>   |
| DIFFUSER          | <ul><li>Heat-resistant polycarbonate lens.</li><li>Uniform light distribution.</li></ul>  |
| CCT & CRI         | • 3000K, 4000K and 5000K.<br>• >80 CRI.   |
| BUG RATED         | <ul> <li>B1-U0-G0</li> <li>B2-U0-G0</li> <li>B2-U0-G2</li> <li>B2-U0-G3</li> <li>B3-U0-G3</li> <li>B4-U0-G4</li> </ul>  |
| WET LOCATION/IP66 | <ul> <li>Ideal for areas with high psi washdown.</li> <li>Rated for outdoor applications.</li> </ul>  |
| MOUNTING SYSTEMS  | <ul> <li>Knuckle Mount (KM), Yoke Mount (YM), Trunnion Mount (TM), Arm Mount Bracket (ARM), Slip Fitter (SF) and NEMA Photocell installation kit (PCKIT).</li> <li>Wall mount adaptor bracket and bullhorns for Slip Fitter.</li> </ul> |
| DLC LISTED        | Premium DLC listed.   |
| EXPECTED LED LIFE | • L70 rated >372,000.   |
| WARRANTY          | • 5 years.  |