



Pluraluce® Indoor, Recessed, Weatherproof & Hazardous

••• FEATURES + BENEFITS

SAMSUNG LED TECHNOLOGY	 Improved lumen maintenance with over 50,000 hour lamp life High lumen output with lower wattage consumption
UP TO 845 LUMENS IN EMERGENCY MODE AND NORMALLY ON	 Greater fixture to fixture spacing Up to 60' spacing on center Cost savings as less units are required
INTERCHANGEABLE OPTICS	Custom designed to deliver maximum outputChoice of symmetric or asymmetric distribution
SURFACE & RECESSED MOUNTING	Suitable for use in a variety of environments
HT, SA & SE CONFIGURATIONS	 Provides lighting in normal conditions as well as in power outages Unique option to have one fixture for all your lighting requirements
NI-MH BATTERIES	Provides 90 or 120 minute emergency durationMaintenance free long life
AUTO-TEST SELF-DIAGNOSTICS	 Intelligent communication with continuous status updates Option to manually run a 30 second, 15 minute or 90 minute test
NEW OR RETROFIT RECESSED CONSTRUCTION	Expands installation areasSuitable for shallow plenum ceilings
NEMA 4X MODEL	Protection against moisture, dust and corrosionFor installation both indoors or outdoor
HAZARDOUS CLASSIFICATION	 Class I, Division 2, Groups A-D, Class II, Division 2, Groups E-G and Class III For areas with explosive gas or dust