

BS730

- The four piece extruded aluminum ballast housing is designed for suspension cable or single pendant mounting.
- Bengal silver finish standard, other custom colors are available.
- 12" and 16" acrylic refractors and aluminum reflectors are offered. Several refractor types are available.
- Two piece design allows for easy installation and maintenance.



APPLICATION: The DRACO® BS730 is ideal for retail, open ceiling areas, loft style offices, cafes and residential installations.

CONFIGURATIONS

MODEL	LAMPS SELECTION (CF)	REFRACTOR	MOUNTING	INPUT	OPTIONS
BS720CF	COMPACT FLOURESCENT	12ACT (12" acrylic clear)	AC_6 (aviation cable)	120V	CCH (custom color housing)
BS720MH	# LAMPS	12ART (12" acrylic red)	SPK_6 (single pendant kit)	277V	SPCW (spiral cord white)
	1	12ABT (12" acrylic blue)	SVL (swivel pendant kit)	120/277V ⁵	SPCB (spiral cord black)
	2	12AGT (12" acrylic green)		347V	CR (custom refractor)
	3	12AAT (12" acrylic amber)			EM (650 lumen 1 lamp)
	4 ¹	12AL (12" aluminum)			QRS* (quartz restrike)
		16ACT ⁴ (16" acrylic clear)			QRSTD ⁷ (QRS with time delay)
		16AL (16" aluminum)			
	NOTE ¹ : 4 lamp version requires 16" refractor.	NOTE ² : 4L-42W requires Osram Lamps	NOTE ³ : custom colors are available for 16" refractor, longer lead times apply.	NOTE ⁵ : specify length for AC & SPK, min 6".	NOTE ⁷ : QRS & QRSTD available on MH units only.

HOUSING: Extruded aluminum construction with powder coated Bengal Silver standard. Custom finishes including painting and anodizing are available.

REFRACTOR: 12" acrylic translucent prismatic refractor available in clear (ACT), red (ART), blue (ABT), green (AGT), and amber (AAT). Also available in spun aluminum (AL). 16" acrylic translucent prismatic design available in clear (ACT). Also available in aluminum (AL); All colors are also available for the 16" as custom.


LAMP/SOCKET: (1-4) 26W, 32W, or 42W GX24q series base CF lamp. (lamp(s) not included).

MOUNTING: Aviation cable (AC) length is to be specified. In field full adjustability. The kit comes complete with a 1/4" deep, 5" diameter white canopy. Single pendant mount (SPK) as standard measures 3/8" IPS (other dimensions are available). The standard flat canopy measures 5" in diameter and is finished in white. A swivel mount pendant (SVL) features 45 rotation.

POWER LINE/FEED: 18/4 SJT straight white cord, 60" long, cord may be field cut. Power line / feed attached to housing for all mounting types.


WARRANTY: 5 year warranty, see website for full warranty details.

Draco BS730 16.22"



DRACO 730 MD

Draco BS730 12.35"



DRACO 730 SM