

GRAN BELLA BS820 FLUORESCENT



Suspended Luminaire

Application: The GRAN BELLA™ BS820 compact fluorescent

Combining architectural design, industrial durability and high efficiency; the GRAN BELLA™ BS820CF is the definitive high-bay solution. The one-piece spun aluminum ballast housing has been designed for both suspension cable and pendant mounting. A 22" prismatic acrylic refractor is standard on all GRAN BELLA™ BS820CF luminaires. The bottom aluminum trim ring assists in overall light control. Additional refractor types are available. The GRAN BELLA™ BS820CF is ideal for warehouses, gymnasiums, arenas and other high ceiling environments.

Type: _____
y l i m a f y a b h g i h E C

Project: _____

CONFIGURE:

a	b	c	d	e	f	g
MODEL	LAMPS	REFRACTOR	MOUNTING	INPUT	FINISH	OPTIONS
BS820CF GRAN BELLA™ BS820 CF SERIES	626W 6x26W CF 632W 6x32W CF 642W 6x42W CF 826W 8x26W CF 832W 8x32W CF 842W 8x42W CF	22ACT 22" acrylic clear 22AL 22" aluminum	AC50 cable 50" AC72 cable 72" AC100 cable 100" AC150 cable 150" AC250 cable 250" PK12 pendant 12" PK18 pendant 18" PK24 pendant 24" PK36 pendant 36" PKCL custom pendant <small>NOTE (1): SVL for swivel pendant NOTE (2): AC is fully adjustable</small>	120V 277V 120/277V 347V	AL aluminum WT white BK black	CCH custom color housing SPCW spiral cord white SPCB spiral cord black 2CK two level switching 3CK three level switching SL safety lens <small>NOTE (1): for custom color specify color code or sample</small>
MODEL a	LAMPS b	REFRACTOR c	MOUNTING d	INPUT e	FINISH f	OPTIONS g
BS820CF						

HOUSING: 5052-H32 spun aluminum construction available with raw clear coat finish, white powdercoat finish or black powdercoat finish as standard. Custom finishes available.

REFRACTOR: 22ACT acrylic translucent prismatic design, also available in spun aluminum (AL).

LAMP/SOCKET: (6 - 8) 26W, 32W or 42W GX24q series base CF lamp (Lamps not included).

MOUNTING: AC50 luminaire to have 5" diameter white canopy. AC72 72" aviation cable, adjustable. AC100 100" aviation cable, adjustable. AC150 150" aviation cable, adjustable. AC250 250" aviation cable, adjustable. PK12 12" pendant 1/2" IPS, PK18 18" pendant 1/2" IPS, PK24 24" pendant 1/2" IPS, PK36 36" pendant 1/2" IPS, PKCL custom pendant length, diameter and finish. SVL swivel pendant connector has 45° rotation and 75lbs maximum load. Aviation cable mount uses 1/4" deep, 5" diameter white canopy. Pendant

Canopies mount to standard 4" octagonal junction box supplied by others.

POWER LINE/FEED: 18/4 SJT straight white cord, 60" long, cord may be field cut. Power line / feed attached to housing for all mounting types.

ALUMINUM TRIM: 5052 decorative support bottom control ring suspended by four (4) color matched, formed aluminum support arms.

