# **PACO REMOTE**

UL) LISTED

Job/Location:Job Type:Contractor:Job Type:Prepared By:Date:








## paco - high output led remote heads


The PACO, fully adjustable remote heads utilizes high output LED technology. For use as part of an emergency lighting system, providing light for path of egress. Weather-proof version is sealed for use in damp and wet location areas.


#### electrical

The operating temperature is from 68°F up to 86°F (20°C up to 30°C).

## dimensions (in,mm.)







Series	Α	В	C
PR-1	4.6"	4.6 "	2.5"
	116mm	116mm	63mm
PR-2	6.7"	4.7 "	2.5 <sup>"</sup>
	179mm	119mm	63mm
PR-WP	4.5" 179mm	4.5 <sup>"</sup>	5.8 <sup>"</sup> 63mm

## ordering logic

Series	Head #	Options
PR	1 <sup>1</sup> (single head)	B <sup>2</sup> (black housing)
	2 <sup>1</sup> (double head)	

#### ordering logic - weather proof

- or a or mig rogio around proof				
Series	Head #	Options		
PR-WP	1 <sup>1</sup> (single head)	B <sup>2</sup> (black housing)		
	2 <sup>1</sup> (double head)			

NOTE 1: 12 LED per head.

NOTE 2: Minimum order quantity required. Contact factory.

EXAMPLE: PR-1

DESCRIPTION: Single remote head, 3.6V, 0.6W



1/16/19

\_\_\_\_\_ www.beghelliusa.com