

TOPLIGHT COMBO (GREENHOUSE SERIES)

- **FIORE TOPLIGHT COMBO:** The combo series is available in different sizes and powers. These features allow the growers to choose the best solution both in case of new installation or in case of replacement of existing HPS lamps.
- **FIORE TOPLIGHT COMBO:** The combo series reproduces the intensity and the luminous spectrum necessary to stimulate the growth and the harmonious development of the plants.
- **HOUSING:** Aluminum body and tempered glass.
- **EFFICIENCY:** Up to 3.1 $\mu\text{mol}/\text{J}$ @ TLed = 77°F (25°C) with "hortis evo" spectrum.
Up to 2.8 $\mu\text{mol}/\text{J}$ @ TLed= 77°F (25°C) with "extended white" spectrum.
- **POWER CONSUMPTION:** LO: 300W
HO: 600W
- **POWER SUPPLY:** 90-305V; 50/60 Hz
180-528V; 50/60 Hz
249-528V; 50/60 Hz
- **OPERATING TEMPERATURE:** 14°F up to 104°F (-10°C up to 40°C)
- **WEIGHT:** LO: 13.22 lbs / 6 kg
HO: 22.04 lbs / 10 kg




- **APPLICATIONS:** Indoor farms and green houses.
- **WARRANTY:** 5 year warranty.

CONFIGURATIONS

MODEL	OPERATION	OUTPUT	SPECTRUM	DISTRIBUTION	INPUT	MOUNTING
FIORE-TOPLIGHT-COMBO	HT (AC only)	LO	HORTIS EVO	WBD (120°)	90-305V	AC (aviation cable)
		HO	EXTENDED WHITE		180-528V	CH (chain hang kit)
					249-528V	

DIMENSIONS




PERFORMANCE

MODEL	POWER CONSUMPTION (W)	PPF ($\mu\text{mol}/\text{sec}$)	LED TOTAL NUMBER ⁽¹⁾	TOTAL HARMONIC DISTORTION	L70 (hrs)
FIORE-TOPLIGHT-COMBO-HT-LO	300	840	1288	<20%	>50,000
FIORE-TOPLIGHT-COMBO-HT-HO	600	1680	2576	<20%	>50,000

NOTE1: PCB with NTC sensor board.

LIGHT DISTRIBUTION



■ **WARRANTY:** 5 year warranty.