

Type: _____

Project: _____

CASTEX 700



HAZARDOUS EXIT SIGN

- The **CASTEX 700** is a hazardous location edge-lit exit sign constructed of die-cast, copper-free aluminum in a gray finish with surface mounting as standard. This sign is UL 844 and UL 924 Listed and rated for use in:

- Class I, Division 1, Groups B, C, D
- Class I, Division 2, Groups A, B, C, D
- Class II, Division 1, Groups E, F, G
- Class II, Division 2, Groups F, G
- Class III

- **INPUT:** 120 to 277VAC

- **BATTERY:** Lithium ion phosphate battery

- **POWER:** 5W (3W available, consult factory)

- **EM OPERATION:** 3 hours

- **HOUSING:** Die-cast A356T6 aluminum (<0.4% copper) with baked-on gray epoxy finish and stainless steel hardware

- **PANEL:** Tempered glass with red LEDs and dual chevrons (consult factory for alternate configurations)

- **OPERATING TEMP:** - 40°F to 140°F (-40°C to 60°C)

- **EM BATTERY OPERATING TEMP:** -4°F to 140°F (-20°C to 60°C)

- **CRI:** >70

- **INSTALLATION:** Wall and pendant mounting standard; 3/4" NPT hubs provided for conduit feed



- **APPLICATION:** The **CASTEX 700** is ideal for oil and gas industry, chemical industry, ocean, marine and aerospace field, metal treatment, food and alcohol industry, high humidity, high vapor, high dust and high temperature locations.

- **WEIGHT:** 13.2 lbs (6 kg)

ORDERING INFORMATION


MODEL ¹	DESCRIPTION	ACCESSORIES
HZ CAS700SARHO120-277	Edgelit exit, 5W self-powered, red led, white double face panel, left & right chevrons, gray, 120-277V	HZJBOX (hazardous rated jbox)
HZ CAS700SAGHO120-277	Edgelit exit, 5W self-powered, green led, mirror single face panel, left & right chevrons, gray, 120-277V	HZPK12 ² (12" pendant stem)
		SW ¹ (special wording- specify)

NOTE 1: Consult factory for make-to-order


NOTE 2: 12" steel pipe, 3/4" NPT

NOTE: Surface/wall mount is standard

DIMENSIONS



MOUNTING OPTIONS



■ **WARRANTY:** 5 years, see website for full warranty details.