

ACCIAIO COMPARISON

■ ■ ■ BX910ECO, 910, 920, 940, 9102SE

ACCIAIO PORTFOLIO	BX910ECO	BX910	BX920	BX940	BX9102SE
Length	4ft	4ft & 2ft	4ft	4ft	2ft
Operation HT (AC only), SA (AC & EM), SE (EM only)	HT, SA	HT, SA	HT, SA	HT, SA	SE
Housing Construction	24ga steel	24ga steel 24ga stainless	24ga steel 24ga stainless	24ga steel 24ga stainless	24ga steel
End Caps	Plastic	Die-cast aluminum	Die-cast aluminum	Die-cast aluminum	Die-cast aluminum
Diffuser	4mm (polycarb) 4mm (glass)	4mm (polycarb) 4mm (glass)	4mm (polycarb) 4mm (glass)	4mm (glass)	4mm (polycarb) 4mm (glass)
Finish (Zinc enriched polyester powder coat)	Grey (RAL7040) White (RAL9003)	Grey (RAL7040) White (RAL9003)	Grey (RAL7040) White (RAL9003)	Grey (RAL7040) White (RAL9003)	Grey (RAL7040) White (RAL9003)
Emergency back-up (Integral, 90min duration, T20 CEC compliant)	1417 lumens (10W)	1417 lumens (10W)	1417 lumens (10W)	1417 lumens (10W)	1729 lumens (10W)
Wattage	30W, 50W	20W, 30W, 50W, 60W	50W, 80W	100W, 160W	10W
Lumens	3543 - 7155	2585 - 8773	6912 - 11,704	12,911 - 21,856	1729
Color Temperature	3000K 4000K 5000K	3000K 4000K 5000K	3000K 4000K 5000K	3000K 4000K 5000K	4000K
Input voltage	120 - 277V 347V	120 - 277V 347V	120 - 277V 347 - 480V	120 - 277V 347 - 480V	120 - 277V
Sensors	Yes	Yes	Yes	Yes	No