

BX940

BX920

BX910

BX910-EC0

BX910SE



• • • features + benefits

FULL PERFORMANCE RANGE	 4000 lumens up to 21,900 lumens 125 L/pw up to 173 L/pw
DURABLE STEEL CONSTRUCTION	 24 gauge steel housing is standard 24 gauge 304 stainless steel housing available Zinc enriched powder coat finish in grey or white.
IMPACT RESISTANT DESIGN	 4mm frosted polycarbonate diffuser is standard 4mm tempered prismatic glass diffuser is available IK09 impact resistance rated
SERIOUS PROTECTION	 IP66 rated for wet locations. 1450 psi wash down. NEMA 4X rated for outdoor use
FUTURE PROOF TECHNOLOGY	Easy change gear tray allows for upgrades as technology evolves
LABOR SAVINGS DESIGN	 Single point entry eliminates installation errors and simplifies maintenance. 72" 5-conductor 600V pre-connected line cord reduces installation time by 50%.
SANITATION LISTED	Meets rigorous sanitation, electrical safety and performance standards (Splash Zone 2) for food safe applications.
EXTENDED WARRANTY	All ACCIAIO products feature a 7-year warranty.
EMERGENCY BACK-UP	 All ACCIAIO offer integrated emergency solutions (1463 lumens) Remote emergency solutions are available (1305 lumens)
SENSORS & CONTROLS	 External sensors offered Wireless & powerless solutions