



IES INDOOR REPORT

PHOTOMETRIC FILENAME : BL726LEDHTLOASYWT50120-277V_S.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TESTLAB] Photopia 2018.1.0 see: www.ltioptics.com/ies

[ISSUE DATE]

[TEST DATE] Wed Dec 19 09:45:00 2018

[TEST] 1

[MANUFACT] BEGHELLI

[LUMCAT]

[LUMINAIRE] BL726LEDHTLOASYWT50120-277V

[LAMP] LED 0.3W White 2323 package (65mA)

[LAMPCAT] SPMWHT221MD5WAT0S0

[OTHER]

IESNA:LM-63-2002

[TEST] 6,552

[TESTLAB] CSA Group

[ISSUE DATE] 7/24/2013 1:09:24 PM

[OTHER] Luminous shape: Rectangle

[OTHER] Luminous dimensions (feet)

[OTHER] 0 - 180 Axis: 4.2

[OTHER] 90 - 270 Axis: 0.6

[OTHER] Height: 0.1

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	5854
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	117
Total Luminaire Watts	50
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	2.12
Spacing Criterion (90-270)	1.28
Spacing Criterion (Diagonal)	1.54
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	1.01 ft
Luminous Width (90-270)	0.99 ft
Luminous Height	0.36 ft

IES INDOOR REPORT
PHOTOMETRIC FILENAME : BL726LEDHTLOASYWT50120-277V_S.IES

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	41525	34690	14433
55	18642	18338	8175
65	5658	5994	3425
75	1782	1677	1241
85	327	280	325

IES INDOOR REPORT
PHOTOMETRIC FILENAME : BL726LEDHTLOASYWT50120-277V_S.IES

CANDELA TABULATION

	0	10	20	30	40	50	60	70	80	90
0.0	2207.26	2207.26	2207.26	2207.26	2207.26	2207.26	2207.26	2207.26	2207.26	2207.26
2.5	2260.90	2325.28	2319.20	2289.82	2269.47	2246.88	2209.49	2201.58	2098.46	2093.59
5.0	2510.76	2504.50	2486.02	2447.39	2402.52	2360.06	2303.56	2281.05	2171.89	2086.45
7.5	2710.87	2777.31	2703.70	2663.98	2585.91	2528.33	2423.47	2303.72	2178.29	2039.73
10.0	3059.05	3044.02	3000.36	2936.83	2826.77	2697.90	2568.38	2417.69	2245.13	2086.77
12.5	3338.52	3320.39	3260.33	3154.69	3026.23	2897.77	2717.07	2529.35	2319.49	2085.61
15.0	3607.68	3618.82	3523.91	3442.17	3290.09	3088.64	2899.38	2612.86	2382.08	2074.25
17.5	3902.98	3878.40	3796.46	3697.26	3519.27	3274.19	3035.16	2726.30	2407.62	2083.34
20.0	4189.73	4096.93	4054.69	3932.45	3763.79	3493.75	3160.83	2816.66	2479.35	2080.33
22.5	4396.85	4346.09	4273.52	4128.98	3914.15	3665.62	3316.33	2910.93	2501.09	2038.89
25.0	4549.74	4521.22	4459.81	4313.01	4108.09	3798.39	3403.20	2962.11	2489.34	2006.27
27.5	4690.03	4666.60	4613.18	4450.08	4240.13	3928.52	3508.20	3002.39	2511.87	1976.02
30.0	4833.03	4810.93	4724.56	4562.72	4328.89	4010.06	3565.78	3034.42	2478.32	1912.65
32.5	4910.47	4906.57	4817.11	4652.14	4403.68	4038.66	3623.20	3072.99	2459.37	1849.37
35.0	4979.21	4955.38	4867.43	4699.51	4439.85	4037.79	3594.51	3053.18	2420.17	1779.97
37.5	4890.09	4882.05	4811.01	4633.44	4377.64	3992.15	3542.28	2988.18	2340.00	1693.00
40.0	4657.72	4641.38	4609.34	4458.74	4217.57	3873.92	3428.88	2870.06	2218.84	1573.15
42.5	4228.73	4270.57	4229.10	4150.10	3951.93	3635.33	3212.43	2687.14	2070.05	1435.00
45.0	3721.68	3747.58	3773.96	3717.17	3599.45	3326.38	2940.64	2442.89	1887.01	1301.28
47.5	3168.46	3193.13	3224.83	3233.65	3164.52	2947.97	2626.61	2167.63	1661.94	1139.07
50.0	2559.41	2603.77	2662.78	2704.33	2695.37	2551.95	2269.25	1879.70	1423.63	987.42
52.5	1995.88	2036.30	2091.81	2163.75	2188.56	2106.70	1885.72	1564.56	1194.99	822.15
55.0	1508.80	1527.41	1594.16	1668.07	1722.60	1679.09	1526.99	1256.51	956.84	666.70
57.5	1090.47	1119.97	1164.42	1236.70	1296.51	1292.49	1188.64	978.31	754.56	532.56
60.0	777.54	800.69	836.11	901.62	950.33	955.36	887.27	745.45	572.02	414.70
62.5	552.12	565.13	600.96	637.00	685.56	695.83	652.78	556.38	434.57	315.63
65.0	394.83	408.12	424.49	455.37	491.11	502.26	480.28	403.13	316.66	241.38
67.5	287.11	293.88	301.62	321.32	343.77	354.35	339.87	290.49	231.11	182.63
70.0	201.30	207.59	217.86	227.40	239.80	248.53	235.12	207.97	168.58	130.11
72.5	144.51	145.39	155.73	160.34	170.18	172.37	161.19	146.37	120.86	97.49
75.0	100.73	106.37	108.02	115.00	119.03	117.29	111.98	101.50	83.99	71.02
77.5	71.89	73.66	75.11	78.86	81.54	80.61	78.81	69.62	60.96	51.32
80.0	48.89	48.58	49.52	50.62	52.62	53.25	50.27	47.64	41.14	36.55
82.5	29.30	29.58	29.69	30.51	31.36	32.02	31.04	29.18	25.63	23.82
85.0	13.58	13.74	14.21	15.73	16.12	15.18	15.18	14.44	14.69	13.74
87.5	1.02	1.41	1.68	2.14	2.44	2.74	3.14	3.53	3.46	3.14
90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
92.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
95.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
97.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
102.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
105.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
107.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
110.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
112.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
115.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
117.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
120.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
122.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
125.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
127.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
130.0	0.00	0.00	0.00	0.00	0.02	0.00	0.01	0.00	0.00	0.00
132.5	0.00	0.00	0.02	0.02	0.00	0.00	0.00	0.00	0.00	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : BL726LEDHTLOASYWT50120-277V_S.IES

CANDELA TABULATION - (Cont.)

135.0	0.00	0.20	0.11	0.00	0.00	0.00	0.00	0.00	0.00	0.00
137.5	0.00	0.13	0.18	0.02	0.07	0.11	0.05	0.00	0.01	0.01
140.0	0.00	0.08	0.10	0.00	0.02	0.13	0.02	0.00	0.01	0.00
142.5	0.05	0.00	0.01	0.00	0.03	0.00	0.03	0.00	0.00	0.00
145.0	0.01	0.01	0.00	0.00	0.00	0.05	0.00	0.00	0.00	0.00
147.5	0.00	0.00	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00
150.0	0.00	0.00	0.01	0.02	0.01	0.00	0.00	0.00	0.00	0.00
152.5	0.00	0.02	0.05	0.01	0.00	0.00	0.00	0.00	0.00	0.00
155.0	0.00	0.03	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
157.5	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
160.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
162.5	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.05
165.0	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.01	0.05	0.00
167.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
170.0	0.00	0.00	0.00	0.00	0.01	0.01	0.00	0.00	0.00	0.00
172.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
175.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
177.5	0.00	0.00	0.00	0.00	0.04	0.00	0.00	0.00	0.00	0.00
180.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

**Vert.
Angles**

Horizontal Angles

	<u>100</u>	<u>110</u>	<u>120</u>	<u>130</u>	<u>140</u>	<u>150</u>	<u>160</u>	<u>170</u>	<u>180</u>
0.0	2207.26	2207.26	2207.26	2207.26	2207.26	2207.26	2207.26	2207.26	2207.26
2.5	2020.08	1988.19	1979.93	1916.42	1884.54	1818.16	1806.05	1838.87	1805.00
5.0	1981.55	1888.04	1787.86	1691.70	1623.25	1600.92	1541.08	1536.79	1552.07
7.5	1920.62	1795.53	1637.98	1509.28	1447.54	1345.74	1307.75	1276.27	1260.93
10.0	1890.16	1675.40	1549.27	1370.84	1235.47	1128.32	1063.40	1015.54	984.46
12.5	1840.80	1626.63	1394.87	1193.65	1040.59	922.64	858.78	806.77	775.85
15.0	1806.48	1509.23	1239.81	1022.97	860.23	744.76	692.25	641.62	635.04
17.5	1748.17	1390.09	1111.77	877.02	725.34	633.31	566.07	538.81	520.81
20.0	1669.28	1294.38	983.81	761.15	612.77	529.77	500.24	475.10	473.07
22.5	1604.75	1188.05	875.73	656.19	545.64	489.85	471.53	465.66	456.57
25.0	1524.69	1075.18	773.84	592.61	498.51	472.44	461.42	471.71	458.63
27.5	1409.42	987.74	703.08	547.93	491.31	478.64	482.61	484.95	491.36
30.0	1340.61	899.43	631.99	514.71	488.49	489.97	497.45	506.96	506.66
32.5	1258.97	828.13	592.78	509.16	494.91	512.47	526.82	534.98	532.12
35.0	1185.50	757.45	553.38	501.79	504.50	528.64	543.34	544.79	546.83
37.5	1096.58	689.39	533.16	495.80	513.68	530.19	549.10	540.89	545.16
40.0	995.50	632.71	504.34	484.55	512.60	524.86	532.51	529.86	525.96
42.5	904.23	575.87	471.09	473.23	493.24	509.26	509.71	500.57	499.03
45.0	800.70	523.78	443.09	445.68	472.95	477.00	471.88	459.35	462.05
47.5	710.21	474.11	411.44	419.83	430.04	437.30	427.03	419.86	415.20
50.0	626.71	422.21	370.64	379.96	387.21	386.10	373.56	364.40	357.79
52.5	528.91	365.06	325.50	338.71	339.38	334.56	319.92	308.76	308.51
55.0	436.56	315.49	283.53	281.58	287.60	278.77	264.02	258.03	248.50
57.5	356.64	262.86	235.12	237.02	235.26	225.49	214.06	205.95	205.59
60.0	285.04	218.75	192.68	191.62	187.24	179.81	171.29	164.13	164.44
62.5	230.44	175.50	156.68	152.65	147.75	143.75	135.19	131.35	126.46
65.0	176.97	141.10	125.46	120.74	117.68	109.69	104.78	100.80	101.43
67.5	139.42	111.37	98.58	94.62	89.72	83.80	81.48	77.40	78.24
70.0	102.23	87.79	78.44	74.19	69.77	67.11	63.91	59.35	60.49
72.5	81.38	67.55	60.20	59.15	54.94	52.38	48.11	48.22	48.47
75.0	58.86	51.67	45.95	45.10	42.50	40.70	39.63	38.63	36.49
77.5	44.92	38.68	36.04	34.47	32.56	32.76	31.24	29.97	29.68
80.0	30.90	29.94	27.41	26.55	25.40	25.98	25.97	25.38	26.52

IES INDOOR REPORT
PHOTOMETRIC FILENAME : BL726LEDHTLOASYWT50120-277V_S.IES

CANDELA TABULATION - (Cont.)

82.5	21.67	21.19	20.14	20.43	19.76	19.57	20.66	21.05	20.24
85.0	12.20	11.92	12.12	12.93	12.10	12.99	13.89	13.60	14.05
87.5	2.97	3.20	3.48	3.39	3.71	3.83	3.91	4.60	4.44
90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
92.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
95.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
97.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
102.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
105.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
107.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
110.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
112.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
115.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
117.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
120.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
122.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
125.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
127.5	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00
130.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
132.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
135.0	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00	0.00
137.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
140.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
142.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
145.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
147.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
150.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
152.5	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00
155.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
157.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
160.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
162.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
165.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
167.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
170.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
172.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
175.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
177.5	0.00	0.00	0.00	0.05	0.00	0.00	0.00	0.00	0.00
180.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : BL726LEDHTLOASYWT50120-277V_S.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	790.48	N.A.	13.50
0-30	1831.09	N.A.	31.30
0-40	3267.52	N.A.	55.80
0-60	5460.57	N.A.	93.30
0-80	5837.00	N.A.	99.70
0-90	5853.6	N.A.	100.00
10-90	5658.47	N.A.	96.70
20-40	2477.04	N.A.	42.30
20-50	3867.94	N.A.	66.10
40-70	2483.25	N.A.	42.40
60-80	376.43	N.A.	6.40
70-80	86.24	N.A.	1.50
80-90	16.60	N.A.	0.30
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.02	N.A.	0.00
90-180	0.02	N.A.	0.00
110-180	0.02	N.A.	0.00
0-180	5853.62	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	195.14
10-20	595.34
20-30	1040.61
30-40	1436.43
40-50	1390.9
50-60	802.16
60-70	290.19
70-80	86.24
80-90	16.60
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.01
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00


IES INDOOR REPORT
PHOTOMETRIC FILENAME : BL726LEDHTLOASYWT50120-277V_S.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	93	92	90	88
2	103	96	90	85	100	94	89	84	90	86	82	87	84	80	84	81	79	77
3	95	85	78	73	92	84	77	72	81	76	71	78	74	70	76	72	69	67
4	87	77	69	63	85	75	68	62	73	67	62	71	65	61	69	64	60	58
5	80	69	61	55	79	68	60	54	66	59	54	64	58	53	62	57	53	51
6	74	62	54	48	73	61	54	48	60	53	48	58	52	47	56	51	47	45
7	69	56	48	43	67	56	48	42	54	47	42	53	47	42	52	46	42	40
8	64	52	44	38	63	51	43	38	50	43	38	48	42	37	47	42	37	35
9	60	47	39	34	59	47	39	34	46	39	34	44	38	34	43	38	34	32
10	56	43	36	31	55	43	36	31	42	35	31	41	35	30	40	34	30	29

POLAR GRAPH



Maximum Candela = 4979.21 Located At Horizontal Angle = 0, Vertical Angle = 35
1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (0)