



IES INDOOR REPORT

PHOTOMETRIC FILENAME : BL726LEDHTMOWT50120-277V_S.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TESTLAB] Photopia 2018.1.0 see: www.ltioptics.com/ies

[ISSUE DATE]

[TEST DATE] Tue Dec 18 17:09:21 2018

[TEST] 1

[MANUFACT] BEGHELLI

[LUMCAT]

[LUMINAIRE] BL726LEDHTMOWT50120-277V

[LAMP] LED 0.3W White 2323 package (65mA)

[LAMPCAT] SPMWHT221MD5WAT0S0

[OTHER]

IESNA:LM-63-2002

[TEST] 6,552

[TESTLAB] CSA Group

[ISSUE DATE] 7/24/2013 1:09:24 PM

[OTHER] Luminous shape: Rectangle

[OTHER] Luminous dimensions (feet)

[OTHER] 0 - 180 Axis: 4.2

[OTHER] 90 - 270 Axis: 0.6

[OTHER] Height: 0.1

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	8496
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	121
Total Luminaire Watts	70
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.50
Spacing Criterion (90-270)	1.50
Spacing Criterion (Diagonal)	1.42
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	0.99 ft
Luminous Width (90-270)	1.01 ft
Luminous Height	0.36 ft

IES INDOOR REPORT
PHOTOMETRIC FILENAME : BL726LEDHTMOWT50120-277V_S.IES

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	27095	24473	27258
55	13288	11684	13391
65	4765	4053	4812
75	1643	1335	1665
85	402	304	409

IES INDOOR REPORT
PHOTOMETRIC FILENAME : BL726LEDHTMOWT50120-277V_S.IES

CANDELA TABULATION

	<u>0</u>
0.0	3487.99
2.5	3267.75
5.0	3245.01
7.5	3278.55
10.0	3336.49
12.5	3384.51
15.0	3453.32
17.5	3532.13
20.0	3603.73
22.5	3655.47
25.0	3681.34
27.5	3685.93
30.0	3660.18
32.5	3601.51
35.0	3499.16
37.5	3329.53
40.0	3086.75
42.5	2781.74
45.0	2442.95
47.5	2083.31
50.0	1730.88
52.5	1389.87
55.0	1083.72
57.5	823.76
60.0	615.39
62.5	456.30
65.0	335.80
67.5	245.13
70.0	177.37
72.5	129.27
75.0	94.07
77.5	67.61
80.0	48.06
82.5	31.52
85.0	17.00
87.5	3.98
90.0	0.00
92.5	0.00
95.0	0.00
97.5	0.00
100.0	0.00
102.5	0.00
105.0	0.00
107.5	0.00
110.0	0.00
112.5	0.00
115.0	0.00
117.5	0.00
120.0	0.00
122.5	0.00
125.0	0.00
127.5	0.00
130.0	0.00
132.5	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : BL726LEDHTMOWT50120-277V_S.IES

CANDELA TABULATION - (Cont.)

135.0	0.01
137.5	0.02
140.0	0.03
142.5	0.01
145.0	0.00
147.5	0.00
150.0	0.00
152.5	0.00
155.0	0.00
157.5	0.00
160.0	0.00
162.5	0.00
165.0	0.00
167.5	0.00
170.0	0.00
172.5	0.00
175.0	0.00
177.5	0.00
180.0	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : BL726LEDHTMOWT50120-277V_S.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	1298.68	N.A.	15.30
0-30	2995.26	N.A.	35.30
0-40	5156.26	N.A.	60.70
0-60	8016.11	N.A.	94.30
0-80	8475.39	N.A.	99.80
0-90	8496.19	N.A.	100.00
10-90	8182.33	N.A.	96.30
20-40	3857.59	N.A.	45.40
20-50	5724.38	N.A.	67.40
40-70	3212.86	N.A.	37.80
60-80	459.28	N.A.	5.40
70-80	106.27	N.A.	1.30
80-90	20.81	N.A.	0.20
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.01	N.A.	0.00
90-180	0.01	N.A.	0.00
110-180	0.01	N.A.	0.00
0-180	8496.21	N.A.	100.00

Total Luminaire Efficiency = N.A.%

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	313.86
10-20	984.82
20-30	1696.58
30-40	2161.01
40-50	1866.79
50-60	993.05
60-70	353.02
70-80	106.27
80-90	20.81
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.01
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00


IES INDOOR REPORT
 PHOTOMETRIC FILENAME : BL726LEDHTMOWT50120-277V_S.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	111	108	104	101	109	105	102	100	101	99	97	97	96	94	94	92	91	89
2	103	97	91	86	101	95	90	85	91	87	84	88	85	82	85	82	80	78
3	96	87	80	75	93	85	79	74	82	77	73	80	75	71	77	74	70	68
4	88	78	71	65	86	77	70	64	74	68	64	72	67	63	70	66	62	60
5	82	71	63	57	80	70	62	57	68	61	56	66	60	56	64	59	55	53
6	76	64	56	50	74	63	56	50	61	55	50	60	54	49	58	53	49	47
7	71	58	50	45	69	58	50	45	56	49	44	55	49	44	54	48	44	42
8	66	53	46	40	64	53	45	40	52	45	40	50	44	40	49	44	40	38
9	62	49	42	36	60	49	41	36	47	41	36	46	40	36	45	40	36	34
10	58	45	38	33	56	45	38	33	44	37	33	43	37	33	42	37	33	31

POLAR GRAPH



Maximum Candela = 3685.93 Located At Horizontal Angle = 0, Vertical Angle = 27.5
1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (0)