



BOXLED® MINI

■ ■ ■ features + benefits

HOUSING	<ul style="list-style-type: none"> • Die-cast aluminum housing with zinc enriched polyester gray (RAL7040) powder coat. • Chemical, flame and corrosion resistant. • 316 stainless steel latches and hardware.
CERTIFICATIONS	<ul style="list-style-type: none"> • Wet location / IP66 / NEMA 4x for integrity and ingress control. • IK09 rated for impact resistance. • 3G rated for vibration resistance. • Title 24 compliant. • Splash Zone 2 sanitation compliant.
MOUNTING	<ul style="list-style-type: none"> • Six (6) mounting configurations allow great flexibility in design.
OPERATING TEMPERATURE	<ul style="list-style-type: none"> • Ideal for trying environments. • -30°C to +40°C (-22°F to +104°F).
DIMMING	<ul style="list-style-type: none"> • 0-10V Dimming. • Compatible with most dimming systems.
ADJUSTABLE OPTICS	<ul style="list-style-type: none"> • Polished aluminum symmetric reflector with field installable asymmetric mod.
DIFFUSER	<ul style="list-style-type: none"> • 4mm tempered glass lens provides impact resistance and glare.
EXPECTED LED LIFE	<ul style="list-style-type: none"> • L70 rated >60,000.
WARRANTY	<ul style="list-style-type: none"> • 5 years.