



LEDLUMINA BS400

■ ■ ■ features + benefits

PERFORMANCE	<ul style="list-style-type: none"> • Up to 126 lm/w. • 3570 up to 7282 lm. • 30W (LO), 45W (MO) and 60W (HO) versions offered.
QUICK INSTALLATION	<ul style="list-style-type: none"> • Simple installation saves time. • 72" cord. • Twist lock mounting.
HOUSING	<ul style="list-style-type: none"> • High grade die-cast aluminum with gray powder coat finish.
DIFFUSER	<ul style="list-style-type: none"> • UV stabilized polycarbonate frosted lens reduces glare. • Uniform light distribution.
CCT & CRI	<ul style="list-style-type: none"> • 3000K, 4000K and 5000K. • >80 CRI.
WET LOCATION / IP66	<ul style="list-style-type: none"> • Ideal for areas with high psi washdown. • Rated for outdoor applications.
MOUNTING SYSTEM	<ul style="list-style-type: none"> • Surface mount (standard), Aviation Cable (AC), Chain Hang Kit (CH), Pendant Kit (PK), Swivel Pendant Kit (SVLPK) and Trunnion Mount (TM).
CONTROL READY	<ul style="list-style-type: none"> • Available with integrated sensors.
DLC LISTED	<ul style="list-style-type: none"> • DLC listed in the following categories: Parking Garage Luminaires & Low Bay Luminaires for Commercial and Industrial Buildings.
EXPECTED LED LIFE	<ul style="list-style-type: none"> • L70 rated >60,000.
WARRANTY	<ul style="list-style-type: none"> • 10 years.