

Type: _____

Project: _____

CASTEX



TITLE
24



HIGH BAY

- **CASTEX** is a hazardous location LED lighting fixture Class I Division 2, Groups A,B,C and D; Group II, Zone 1 & Zone 2; Zone 21 & 22.
- The **CASTEX** comes standard in gray with a surface/wall mount bracket.
- **HOUSING:** aluminum alloy.
- **COLOR TEMPERATURES:** 3000K and 5000K (check availability in chart below)
- **LUMENS:** **LO:** 3000 lm **MO:** 11000lm **HO** 20000 lm
- **OPERATING TEMP:** HT (AC Only) -40°F up to 122°F (-40°C to 50°C)
- **WEIGHT:** **LO:** 8.8 lbs/ 3.9 kg **MO:** 11 lbs/ 4.9 kg **HO:** 17 lbs/ 7.7 kg




APPLICATION: The **CASTEX** is ideal for heavy industry, mining, refineries, chemical industry, coastal marine facilities and corrosive applications.

CONFIGURATIONS (while supplies last)

MODEL	ITEM	DESCRIPTION	QTY AVAILABLE
(C1D2, Groups A,B,C & D; Group II, Zones 1 & 2; Zones 21 & 22; IP67; IK09)			
CAS HT LO WT30 WBD 120 277V	117102343	AC only, 30W, 3000K	56
CAS HT MO WT30 WBD 120 277V	117102346	AC only, 100W, 3000K	12
CAS HT HO WT50 WBD 120 277V	117102351	AC only, 200W, 3000K	11


TECHNICAL INFORMATION



MOUNTING OPTIONS


STANDARD

MB (surface wall/mount bracket)
(AIMABLE 90° BOTH SIDES -22.5° INCREMENTS)




OPTIONAL

PK (pendant kit)
(TYP. 12", 24", 48", other specify)



DIMENSIONS



ELECTRICAL RATING

PRODUCT	NOMINAL POWER (W)	AC CURRENT (A)		FREQUENCY (Hz)	DC VOLTAGE (V)	DC CURRENT (mA)
		AC VOLTAGE 120V	277V			
CAS-HT-MO	100	0.85	0.37	51/60	38	2100
CAS-HT-HO	200	1.7	0.74	50/60	40	4600

DIMMER COMPATIBILITY

DIMMER	COMPATABILITY	
	ON / OFF	DIMMING
LEVITON - AWRMG-7	YES	YES
LUTRON - DIVA DVSTV	YES	YES

■ **WARRANTY:** 5 years warranty, see website for full warranty details.