



CASTEX 150



... features + benefits

HAZARDOUS CLASSIFICATIONS	<ul style="list-style-type: none"> • Class I, Division 1, Groups C, D • Class I, Division 2, Groups A, B, C, D • Class II, Division 1, Groups E, F, G • Class II, Division 2, Groups F, G • Class III
PERFORMANCE RANGE	<ul style="list-style-type: none"> • MO: 30W @ 4200 lm • HO: 40W @ 5600 lm
OPERATING TEMPERATURE	<ul style="list-style-type: none"> • -40°F to 149°F (-40°C to 65°C) • Allows for installation in harsh environments.
DURABLE CONSTRUCTION	<ul style="list-style-type: none"> • Die-cast copper free aluminum • Provides added durability for installations in corrosive environments.
IMPACT RESISTANT DESIGN	<ul style="list-style-type: none"> • IK10 resistant design protects the product from high-impact forces cause by natural or human occurrences.
SERIOUS PROTECTION	<ul style="list-style-type: none"> • Rated NEMA 4X which allows it to be protected against the ingress of solid foreign objects (windblown dust) and harmful effects on the equipment due to the ingress of water and other liquids. • Rated IP66 making it suitable for installations in wet and dust filled locations.
MULTIPLE MOUNTING OPTIONS	<ul style="list-style-type: none"> • Pendant Kit • Wall / Surface
WARRANTY	<ul style="list-style-type: none"> • 5 Years