



# CASTEX 510



## ... features + benefits

HAZARDOUS CLASSIFICATIONS	<ul style="list-style-type: none"> <li>• Class I, Division 2, Groups A, B, C, D</li> <li>• Class II, Division 1, Groups E, F, G</li> <li>• Class II, Division 2, Groups F, G</li> <li>• Class III</li> </ul>
PERFORMANCE RANGE	<ul style="list-style-type: none"> <li>• LO: 40W @ 5600 lm</li> <li>• MO: 60W @ 8400 lm</li> <li>• HO: 80W @ 12000 lm</li> </ul>
OPERATING TEMPERATURE	<ul style="list-style-type: none"> <li>• -40°F to 140°F (-40°C to 60°C)</li> <li>• Allows for installation in harsh environments.</li> </ul>
DURABLE CONSTRUCTION	<ul style="list-style-type: none"> <li>• Die-cast copper-free aluminum</li> <li>• Provides added durability for installations in corrosive environments.</li> </ul>
IMPACT RESISTANT DESIGN	<ul style="list-style-type: none"> <li>• <b>IK10</b> resistant design protects the product from high-impact forces cause by natural or human occurrences.</li> </ul>
SERIOUS PROTECTION	<ul style="list-style-type: none"> <li>• Rated <b>NEMA 4X</b> which allows it to be protected against the ingress of solid foreign objects (windblown dust) and harmful effects on the equipment due to the ingress of water and other liquids.</li> <li>• Rated <b>IP66</b> making it suitable for installations in wet and dust filled locations.</li> </ul>
MULTIPLE MOUNTING OPTIONS	<ul style="list-style-type: none"> <li>• Wall / Surface</li> </ul>
WARRANTY	<ul style="list-style-type: none"> <li>• 5 Years</li> </ul>