IP / NEMA Rating Charts

ENCLOSURE PROTECTION RATING SYSTEMS

The International Electrotechnical Commission (IEC) has established an enclosure grading system that produces an IP rating. Many Beghelli products are rated in accordance with the IEC standards and display the IP rating they have achieved. The IP rating is a critical element for emergency lighting fixtures. Since emergency lighting fixtures are typically mounted in close proximity to sprinkler heads (for example wall mounted battery units along a corridor), the potential of water related damage arising from activated or damaged sprinkler heads is an important consideration. The IP / NEMA rating charts below are designed to show the correlation between the IP and NEMA rating systems. Important to note is that NEMA claims that because IEC 60529-1 does not specify protection against corrosion, rust, oil or coolants, a direct correlation between the standards cannot be made. Because the NEMA rating meets or exceeds the corresponding IP rating, you can only translate NEMA to IP, not IP to NEMA. The following table outlines the IP system of enclosure ratings:

0	No Protection	0	No Protection
1	Protection against solid objects up to 50mm, (accidental touch by hands).	1	Protection against vertically falling drops of water (condensation).
2	Protection against solid objects up to 12.5mm, (fingers)	2	Protection from vertical drops of water when tilted at 15 degrees
3	Protection against solid objects over 2.5mm, (tools & wires).	3	Protection from vertical water spray up to 60 degrees (limit 3 minutes)
4	Protected against solid objects over 1mm (wires & nails)	4	Protection against water splashes from any direction, (limited ingress permitted)
5	Protection against dust, (limited ingress, no harmful deposit)	5	Protection against low pressure jets of water from any direction, (causes no harmful effects)
6	The unit is dust-tight	6	Protection against strong jets of water from all directions (no harmful effects)
		7	Protection against the effects of immersion between 15cm and 1m for up to 30 min
		8	Protection against the effects of temporary immersion in water
		9	Protection against high pressure and high temperature water jets from any direction
		9K	Protection against close range, high pressure and high temperature spray

NEMA Enclosures

NEMA uses a standard rating system that defines the types of environments in which an electrical enclosure can be used, and signifies a fixed enclosure's ability to withstand certain environmental conditions.

NEMA 1

- Indoor use to provide a degree of protection to personnel against access to hazardous parts
- To provide a degree of protection of the equipment inside the enclosure against ingress of solid foreign objects (falling dirt)

NEMA 3

- Indoor or outdoor use to provide a degree of protection to personnel against access to hazardous parts
- To provide a degree of protection of the equipment inside the enclosure against ingress of solid foreign objects (falling dirt and windblown dust)
- To provide a degree of protection with respect to harmful effects on the equipment due to the ingress of water (rain, sleet, snow)
- And that will be undamaged by the external formation of ice on the enclosure

NEMA 3R

- Enclosures constructed for either indoor or outdoor use to provide a degree of protection to personnel against access to hazardous parts
- To provide a degree of protection of the equipment inside the enclosure against ingress of solid foreign objects (falling dirt)
- To provide a degree of protection with respect to harmful effects on the equipment due to the ingress of water (rain, sleet, snow)
- And that will be undamaged by the external formation of ice on the enclosure

NEMA 4

- Indoor or outdoor use to provide a degree of protection to personnel against access to hazardous parts
- To provide a degree of protection of the equipment inside the enclosure against ingress of solid foreign objects (falling dirt and windblown dust)
- To provide a degree of protection with respect to harmful effects on the equipment due to the ingress of water (rain, sleet, snow, splashing water, and hose directed water)
- And that will be undamaged by the external formation of ice on the enclosure

NEMA 4X

- Indoor or outdoor use to provide a degree of protection to personnel against access to hazardous parts
- To provide a degree of protection of the equipment inside the enclosure against ingress of solid foreign objects (windblown dust)

- To provide a degree of protection with respect to harmful effects on the equipment due to the ingress of water (rain, sleet, snow, splashing water, and hose directed water)
- That provides an additional level of protection against corrosion
- And that will be undamaged by the external formation of ice on the enclosure

NEMA 6

- Indoor or outdoor use to provide a degree of protection to personnel against access to hazardous parts
- To provide a degree of protection of the equipment inside the enclosure against ingress of solid foreign objects (falling dirt)
- To provide a degree of protection with respect to harmful effects on the equipment due to the ingress of water (hose directed water and the entry of water during occasional temporary submersion at a limited depth)
- And that will be undamaged by the external formation of ice on the enclosure

NEMA 6P

- Indoor or outdoor use to provide a degree of protection to personnel against access to hazardous parts
- To provide a degree of protection of the equipment inside the enclosure against ingress of solid foreign objects (falling dirt)
- To provide a degree of protection with respect to harmful effects on the equipment due to the ingress of water (hose directed water and the entry of water during prolonged submersion at a limited depth)
- That provides an additional level of protection against corrosion and that will be undamaged by the external formation of ice on the enclosure.

NEMA 12

- Constructed (without knockouts) for indoor use to provide a degree of protection to personnel against access to hazardous parts
- To provide a degree of protection of the equipment inside the enclosure against ingress of solid foreign objects (falling dirt and circulating dust, lint, fibers, and flyings)
- And to provide a degree of protection with respect to harmful effects on the equipment due to the ingress of water (dripping and light splashing)

NEMA Enclosures

COMPARISON OF SPECIAL APPLICATIONS OF ENCLOSURES FOR NON-HAZARDOUS LOCATIONS

Provides a degree of protection against			Types of Enclosures										
the following environmental conditions	1*	2*	4	4X	5	6	6P	12	12K	13			
Access to hazardous parts	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х			
Ingress of solid falling objects (falling dirt)	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х			
Ingress of water (drip and light splashing)	-	Х	Х	Х	Х	Х	Х	Х	Х	Х			
**Ingress of solid foreign objects (circulating dust, lint, fibers and flyings)	-	-	Х	Х	-	Х	Х	Х	Х	Х			
**Ingress of solid foreign objects (settling airborne dust, lint, fibers & flyings)	-	-	Х	Х	Х	Х	Х	Х	Х	Х			
Ingress of water (hose down and splashing water)	-	-	Х	Х	-	Х	Х	-	-	-			
Oil and coolant seepage		-	-	-	-	-	-	Х	Х	Х			
Oil or coolant spraying and splashing		-	-	-	-	-	-	-	-	Х			
Corrosive agents		-	-	Х	-	-	Х	-	-	-			
Ingress of water (occasional temporary submersion)		-	-	-	-	Х	Х	-	-	-			
Ingress of water (occasional prolonged submersion)		-	-	-	-	-	Х	-	-	-			
*Rain, snow and sleet		Х	Х	Х	-	Х	Х	-	-	-			
Windblown dust	-	Х	Х	Х	-	Х	Х	-	-	-			

NOTE: *External operating mechanisms are not required to be operable when the enclosure is ice covered **External operating mechanisms are operable when the enclosure is ice covered

