





ACCIAIO® BX SERIES:

NEMA 4X | Wet/IP66 | IK09 | Sanitation | Title 24

comparison chart

	BX910LED-ECO	BX910LED	BX920	BX940	BX9102SE
LENGTH	4ft & 2ft	4ft	4ft	4ft	2ft
OPERATION HT (AC only), SA (AC & EM), SE (EM only)	HT, SA	HT, SA	HT, SA	HT, SA	SE
HOUSING CONSTRUCTION	24ga steel 24ga stainless	24ga steel	24ga steel 24ga stainless	24ga steel 24ga stainless	24ga steel
END CAPS	Die-cast aluminum	Plastic	Die-cast aluminum	Die-cast aluminum	Die-cast aluminum
DIFFUSER	4mm (polycarb) 4mm (glass)	4mm (polycarb) 4mm (glass)	4mm (polycarb) 4mm (glass)	4mm (glass)	4mm (polycarb) 4mm (glass)
FINISH (Zinc enriched polyester powder coat)	Grey (RAL7040) White (RAL9003)				
EMERGENCY BACK-UP (Integral, 90min duration, T20 CEC compliant)	1417 lumens (10W)	1417 lumens (10W)	1417 lumens (10W)	1417 lumens (10W)	1729 lumens (10W)
WATTAGE	30W, 50W	20W, 30W, 50W, 60W	50W, 80W	100W, 160W	10W
LUMENS	3543 - 7155	2585 - 8773	6912 - 11,704	12,911 - 21,856	1729
COLOR TEMPERATURE	3000K 4000K 5000K	3000K 4000K 5000K	3000K 4000K 5000K	3000K 4000K 5000K	4000K
INPUT VOLTAGE	120 - 277V 347V	120 - 277V 347V	120 - 277V 347 - 480V	120 - 277V 347 - 480V	120 - 277V
SENSORS	Yes	Yes	Yes	Yes	No



applications:

The ACCIAIO® BX series is ideal for:

- Warehouses
- Parking Decks
- Farms
 Loading Docks
 Breezeways
 Car Washes

- Pool Areas
- Waste Water Treatment Facilities
- Manufacturing Facilities Gymnasiums























features + benefits

PERFORMANCE	4000 lumens up to 21,900 lumens125 L/pw up to 173 L/pw		
CONSTRUCTION	 24 gauge steel housing is standard 24 gauge 304 stainless steel housing available Zinc enriched powder coat finish in gray or white. 		
IMPACT RESISTANT	 4 mm frosted polycarbonate diffuser is standard 4 mm tempered prismatic glass diffuser is available IK09 impact resistance rated 		
SERIOUS PROTECTION	 IP66 rated for wet locations. 1450 psi wash down. NEMA 4X rated for outdoor use 		
FUTURE PROOF	Easy change gear tray allows for upgrade as technology evolves		
LABOR SAVINGS	 Single point entry eliminates installation errors and simplifies maintenance. 7 2" 5-conductor 600V pre-connected line cord reduces installation time by 50%. 		
SANITATION LISTED	 Meets rigorous sanitation, electrical safety and per formance standards (Splash Zone 2) for food safe applications. 		
EXTENDED WARRANTY	All ACCIAIO products feature a 7-year warranty.		
EMERGENCY BACK-UP	 All ACCIAIO offer integrated emergency solutions (1463 lumens) Remote emergency solutions are available (1305 lumens) 		
SENSORS & CONTROLS	External sensors offeredWireless & powerless solutions		








24 gauge steel housing is standard. Option for 304 stainless steel housing available, along with zinc enriched powder coat in gray or white.





BX910 ECO (left) features twist-lock polycarbonate endcaps. BX910, BX920 (right) and BX940 have die-cast aluminum end caps as standard.



BX910 & BX920 feature a 4mm frosted polycarbonate lens. BX940 has a 4mm prismatic tempered glass lens.



For more information on the ACCIAIO® Famiglia, visit: beghelliusa.com.





Beghelli USA 3810 Executive Way Miramar, Florida 33025 P: 954-442-6600

www.beghelliusa.com