

TURTLE LED - SA

INSTALLATION INSTRUCTIONS



Beghelli USA
3250 Corporate Way
Miramar, Florida 33025 USA
P: 800 726 4316 / P: 954 442 6600
F: 954 442 6677
www.BeghelliUSA.com

TURTLE LED - SA






TITLE TITLE
20 24




IK09 IP65



MODEL INFORMATION



TURTLE LED - SA	
WATTAGE	50W
VOLTAGE	120-277V 50/60Hz
WET LOCATION	YES
OPERATION	HT (AC ONLY)/0-10V DIMMING
AMBIENT TEMPERATURE	0°C(32°F) / 40°C(104°F)
WEIGHT	11 lbs
DIMENSION	50.7" L X 6.7" W X 4.2" H



Parts come separately in a bag.
(851200000)

IMPORTANT SAFEGUARDS

When using electrical equipment, basic safety precautions should always be followed including the following:


READ AND FOLLOW ALL SAFETY INSTRUCTIONS.

1. **CAUTION! ALWAYS MAKE SURE THE POWER IS TURNED OFF** before starting installation.
2. Measure, locate fixture's position, and mark locations for the brackets.
3. Secure brackets to ceiling as shown below. **(HARDWARE BY OTHERS)**
4. Wiring fixture to power supply, shall be performed by a **certified electrician**, and wired in a manner that complies with all local and national electrical codes, as well as the **manufacture's wiring diagram**.
5. Proper replacement of a part removed for user maintenance.

SAVE THESE INSTRUCTIONS!


WARNING ⚠️

No user serviceable parts. Refer service to a qualified service technician. Read instructions prior to installing and/or operating this device. Installation should be performed by a licensed electrician/installer in accordance with local codes.




WIRING DIAGRAM




1. 0-10V dimming wires must be run from a different conduit out of the J-box.




STANDARD INSTALLATION



3. Install cord using provided cord grip as shown below.
4. Connect wires accordingly to the orange terminal connector (black-black; white-white; green-green) by pushing the wires into the terminal as shown.




5. Re-assemble the fixture and install the lens enclosure's clips.



Snap the clips into position.

Hook the clip onto the lens.





Push this portion of the clips horizontally toward the housing to lock the clip in place.


SHIELD INSTALLATION

1. Engage the flange of the Shield (hook) into the rectangular opening on mounting bracket as shown.
2. Install screws as shown on all four corners of shield.

Surface Mounting Clip



Mounting Bracket
Opening
Flange



CAUTION !

PLEASE HANDLE THE SHIELDS WITH PROPER CARE AND DO NOT BEND THE END CAPS. THE SHIELD'S FLANGE AND END CAPS MUST NOT BE DAMAGED OR BENT IN ANY WAY AS IT WILL CAUSE LIGHT LEAKS OR IMPROPER CONNECTION TO THE BRACKET.