





| BX910LED4 LO/HO/VHO | |
|-----------------------------|----------------------------|
| WATTAGE | 30W/50W/60W |
| VOLTAGE | 120-277V/347V 50/60Hz |
| WET LOCATION | YES |
| OPERATION | HT (AC ONLY)/0-10V DIMMING |
| AMBIENT TEMPERATURE (LO,HO) | -40°C (-40°F)/50°C (122°F) |
| AMBIENT TEMPERATURE (VHO) | -40°C (-40°F)/40°C (104°F) |
| WEIGHT | 10 lbs |
| DIMENSION | 47.5" L X 4.3" W X 4.0" H |



1. **CAUTION ! ALWAYS MAKE SURE THE POWER IS TURNED OFF** before starting the installation
2. Measure, locate fixture's position, and mark locations for the brackets.
3. Secure brackets to ceiling as shown below. (HARDWARE BY OTHERS)
4. Wiring fixture to power supply, shall be performed by a **certified electrician**, and wired in a manner that complies with all **local and national electrical codes**, as well as the **manufacturer's wiring diagram**.



- 0-10V DIMMING WIRES MUST BE RUN FROM A DIFFERENT CONDUIT OUT OF THE J-BOX




BEGHELLI USA

3810 Executive Way
Miramar, Florida 33025, USA
Tel: (954) 442-6600
Toll Free: 1 (800) 726-4316

BEGHELLI MÉXICO


Av. del Marqués No. 70 Int.4. Parque
Industrial Bernardo Quintana
CP.76246 El Marqués, Qro, México
Tel: 1 52 (442) 221.62.15/221.64.39

SM - SURFACE MOUNT




1. Snap the fixture onto the pre-installed mounting clips


AC - AVIATION CABLE KIT




1. Attach the cable glider to the mounting clips using provided lock nuts as shown.
2. Snap the assembled mounting clips onto the railing on the housing.
3. Thread the A/C cable through the cable glider as shown. (push top sleeve of cable glider to release lock and adjust level)




CH - CHAIN HANG KIT




1. Insert the hook clip through the loop of the chain
2. Attach the hook clip onto the holes on the top of the mounting clips
3. Snap the fixture to the mounting clips to complete the installation



AM - AIMABLE MOUNT



1. Assemble the swivel brackets as shown
2. Attach the swivel assemblies to the mounting clips
3. Snap the fixture to the mounting clips to complete the installation




BEGHELLI USA

3810 Executive Way
Miramar, Florida 33025, USA
Tel: (954) 442-6600


BEGHELLI MÉXICO

Av. del Marqués No. 70 Int.4. Parque Industrial Bernardo Quintana
CP.76246 El Marqués, Qro, México
Tel: 1 52 (442) 221.62.15/221.64.39


TM - TRUNION MOUNT




1. Attach the Trunion Bracket to the mounting clips as shown.
2. Snap the fixture onto the Trunion Bracket assembly as shown





SB - SEISMIC BRACKET MOUNT



1. Attach the Seismic Brackets to the ceiling before attach the fixture to the brackets
2. Engage the hook of the bracket onto the railing of the housing, then attach the other end with screws and lock washer as shown.



WM - WALL MOUNT




ADDITIONAL DETAILS ON MOUNTING OPTIONS


AC - AIRCRAFT CABLE MOUNT KIT (DAMP LOCATION)



PK - PENDANT KIT (DAMP LOCATION)



CONNECTION BETWEEN FIXTURES FOR ROW MOUNT



LINE UP THE ℓ , ENGAGE THE CONNECTORS TOGETHER, THEN TIGHT THE NUT AS INDICATED ON THE NUT

FOR WET LOCATION J-BOX COVERS (BY OTHERS)




(TYP. 4\"/>



(TYP. 2\"/>



3/8 NPT FEMALE X 1/2 NPT MALE BUSHING REQUIRED



1. WHITE (NEUTRAL)
2. GREEN (GROUND)
3. BLACK (HOT)
4. VIOLET (DIM +)
5. GRAY (DIM -)

ROW MOUNT OPTION
(MAX. RUN DISTANCE FT)
(ONLY FOR CHAIN & AIRCRAFT CABLE)
VARIES



CONTINUOUS ROW MOUNT OPTION
(MAX. RUN DISTANCE FT)
(ONLY FOR CHAIN & AIRCRAFT CABLE)



CONNECTED

BEGHELLI USA

3810 Executive Way
Miramar, Florida 33025, USA
Tel: (954) 442-6600

BEGHELLI MÉXICO

Av. del Marqués No. 70 Int.4. Parque Industrial Bernardo Quintana
CP.76246 El Marqués, Qro, México
Tel: 1 52 (442) 221.62.15/221.64.39