





BX910LED4 LO/MO/HO/VHO	
WATTAGE	30W/45W/50W/60W
VOLTAGE	120-277V/347V 50/60Hz
WET LOCATION	YES
OPERATION	SA (AC/EM)/0-10V DIMMING
AMBIENT TEMPERATURE	-40°C (-40°F)/50°C (104°F)
AMBIENT TEMPERATURE (VHO)	-40°C (-40°F)/40°C (104°F)
WEIGHT	12 lbs
DIMENSION	47.5" L X 4.3" W X 4.0" H



- CAUTION ! ALWAYS MAKE SURE THE POWER IS TURNED OFF** before starting the installation  
MISE EN GARDE! ASSUREZ-VOUS TOUJOURS QUE L'ALIMENTATION EST COUPÉE
- Measure, locate fixture's position, and mark locations for the brackets.
- Secure brackets to ceiling as shown below. (HARDWARE BY OTHERS)
- Wiring fixture to power supply, shall be performed by a **certified electrician**, and wired in a manner that complies with all **local and national electrical codes**, as well as the **manufacturer's wiring diagram**.
- Proper replacement of a part removed for user maintenance.



- 0-10V DIMMING WIRES MUST BE RUN FROM A DIFFERENT CONDUIT OUT OF THE J-BOX



## BEGHELLI USA

3810 Executive Way  
Miramar, Florida 33025, USA  
Tel: (954) 442-6600

## BEGHELLI MÉXICO


Av. del Marqués No. 70 Int.4. Parque  
Industrial Bernardo Quintana  
CP.76246 El Marqués, Qro, México  
Tel: 1 52 (442) 221.62.15/221.64.39

**DO NOT JOIN CONVERTER CONNECTOR UNTIL INSTALLATION IS COMPLETE & AC POWER IS SUPPLIED TO THE EMERGENCY DRIVER**

Remove the (2) screws to access the connection for the battery.



Connect the wires to engage the battery, before power up the fixture.



- **BATTERY NEEDS TO BE CHARGED MINIMUM 24 HRS, BEFORE PERFORMING THE ACTUAL 90 MIN. TEST**

**OPTIONAL MOUNTINGS:** CHAIN HANG KIT, AVIATION CABLE KIT, PENDANT KITS, PIVOT; (SEE SEPARATE **STANDARD INSTALLATION INSTRUCTION** SHEET FOR DETAILS)

**BEGHELLI USA**

3810 Executive Way  
Miramar, Florida 33025, USA  
Tel: (954) 442-6600

**BEGHELLI MÉXICO**

Av. del Marqués No. 70 Int.4. Parque  
Industrial Bernardo Quintana  
CP.76246 El Marqués, Qro, México  
Tel: 1 52 (442) 221.62.15/221.64.39