## BS100LED



•••••

LED linear vapor tight



### BS100LED



Elevate your commercial industrial or outdoor lighting with the **BS100LED** - a 2 and 4-foot, high-performance, linear LED vapor tight solution.

Designed to excel in demanding environments, the **BS100LED** offers unprecedented durability, energy efficiency and versatility to illuminate a wide range of indoor & outdoor commercial applications.


#### **KEY FEATURES**


- 100% UV stabilized polycarbonate gray housing
- Liquid silicone perimeter gasket with memory retention
- Up to 12K lm (3000/3500/4000/5000K)
- Excellent uniformity with NO glare
- Multiple mounting options
- IP66 Quick Mount Bracket option
- Integral battery backup and control options

#### **APPLICATIONS**

- Retail
- Parking Garages
- Industrial
- Carports
- Warehouses
- Breezeways
- Parking Structures
- Schools


#### **DIMENSIONS**







# TECHNICAL IFORMATION



POWER CORD STOW 18/5 OR 18/3 (BY OTHERS)

-M20 LIQUID-TIGHT CORD GRIP

3-POLE QUICK CONNECTOR FOR HOT & NEUTRAL (NOT SHOWN) (5 SOLID 18 AWG WIRES)

INJECTION MODED PLASTIC ENCLOSURE LENS CLIP

ELECTRONIC 0-10V DIMMING DRIVER FOR 120-277V 50/60Hz , 347-480V OPERATION (SYSTEM POWER CONSUMPTION 50W)

(2) MID-POWER WHITE LED PCB

INJECTION MOLDED PLASTIC HOUSING IN GRAY

22 GA. STEEL REFLECTOR IN WHITE POWDER COAT FINISH FLEXIBLE INJECT MOLDED PLASTIC REFLECTOR HOLDER CLIP

FROSTED UV STABILIZED POLYCARBONATED DIFFUSER/ENCLOSURE, PROVIDING EVEN LIGHT DISTRIBUTION