



ILLUMINA COMPARISON

■ ■ ■ BS100, BS100 STEALTH, BS100PG, BS101, BS101ECO, BS101ECOe

Model	BS100	BS100 STEALTH	BS100PG	BS101	BS101ECO	BS101ECOe
Length	4ft & 2ft	4ft	4ft & 2ft	4ft	4ft	4ft
Operation HT (AC only), SA (AC & EM), SE (EM only)	HT, SA	HT, SA	HT, SA	HT, SA	HT, SA	HT, SA
Housing Construction	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate
Diffuser Construction	Frosted Polycarbonate	Frosted Polycarbonate	Frosted Polycarbonate	Frosted Polycarbonate	Frosted Polycarbonate	Frosted Polycarbonate
Mounting Options	12 offered	12 offered	12 offered	11 offered	11 offered	12 offered
Certifications & Approvals	NSF, IP66, BAA DLC PREMIUM, T24	NSF, IP66, BAA DLC PREMIUM, T24	NSF, IP66, BAA DLC PREMIUM, T24	NSF, IP66, BAA DLC PREMIUM, T24	NSF, IP66, BAA DLC PREMIUM, T24	NSF, IP66, BAA DLC PREMIUM, T24
Emergency back-up (Integral, 90 min, T20 CEC compliant)	1573 lm (4 ft) 1022 lm (2 ft)	1573 lm	1474 lm (4 ft) 912 lm (2 ft)	1663 lm	1440 lm	1170 lm
Wattage	30W, 40W, 50W, 60W, 70W	30W, 40W, 50W, 60W, 70W	30W, 40W, 50W, 60W, 70W	40W, 60W	35W, 55W	35W
Lumens	3876 - 11,589	4375 - 11,589	3457 - 9768	5786 - 10,351	4744 - 7919	4090 - 4156
Color Temperature	3000K, 3500K 4000K, 5000K	3000K, 3500K 4000K, 5000K	3000K, 4000K 5000K	3000K, 3500K 4000K, 5000K	3000K, 3500K 4000K, 5000K	4000K 5000K
Input voltage	120 - 277V 347 - 480V	120 - 277V 347 - 480V	120 - 277V 347 - 480V	120 - 277V 347 - 480V	120 - 277V 347 - 480V	120 - 277V
Sensors & Controls	Yes	Yes	Yes	Yes	Yes	Yes
Warranty	5 years	5 years	5 years	5 years	5 years	5 years