



# SCHOOL SOLUTIONS



**BS100LED**

## ILLUMINA VAPOR TIGHT - 2 FT, 4FT

3900 to 11,500 lm / 30W to 70W

UV-stabilized polycarbonate construction

3000K / 3500K / 4000K / 5000K

IP66 quick mount bracket available

Integral battery backup and control options



## BUDGET FRIENDLY LINEAR LIGHTING

3700-5200 lm (4 ft) / 7200-10,000 lm (8 ft)

Selectable wattage (26-70W)

CCT selectable (3500K, 4000K, 5000K)

22 ga steel housing in a white finish

0-10V dimming std, wireless control option



**STRIPLED SELECTABLE**



**SWL SEL (4')**

## STAIRWELL LIGHTING SOLUTION

Power selectable (4200 to 6500 lm / 28-46W)

CCT selectable (3500K / 4000K / 5000K)

Optional occ sensor & battery backup

DLC PREMIUM qualified for stairwells & passageways



## LOW PROFILE HIGH BAY

12,000 to 35,000 lm / 150W, 240W

Die-cast aluminum housing

Multiple mounting options

Egress, controls and high voltage options

Operating temperatures: HT -40°C to +45°C



**BOXLED BL736**



**NUVOLA**

## HIGH BAY LED LUMINAIRE

10,000 to 37,000 lm / 90 to 240W / 120-277V

Durable die-cast aluminum construction

90° & 120° beam distributions

Multiple mounting configurations

>80 CRI







**ACCIAIO BX910LED SE**

## HIGH OUTPUT EMERGENCY SOLUTION

Emergency 1700 lm, up to 80' spacing (18' ht)

Durable 24 gauge steel housing

Polycarbonate diffuser std, tempered glass option

180-degree adjustable mount for ceiling or wall

Nema 4X rated



## EMERGENCY LIGHTING

Durable polycarbonate construction

Fully enclosed heads protect positioning

Surface wall or ceiling mount

Up to 80 ft spacing from 932 lm (5000K CCT)

Autotest optional



**ECCO LUNA LED**

## WET LOCATION EMERGENCY UNIT

Up to 925 lm in emergency mode

90 minutes standard illumination (NiMh)

Up to 42 ft on-center spacing

EM only and AC & EM models

Surface & ceiling mounting options



**TEMPESTA LED ECO**

## VANDAL RESISTANT EXIT SIGN

Heavy duty die-cast aluminum construction

Cold location models: -40°C to 45°C

1/8" impact resistant polycarbonate cover

Slim, architectural design

Universal mounting, autotest optional



## VANDAL RESISTANT COMBO UNIT

Heavy duty die-cast aluminum construction

Cold location models: -40°C to 40°C

1/8" impact resistant polycarbonate cover

Enclosed and protected MR16 LED lamps

Universal mounting, autotest optional





## UNIVERSAL EMERGENCY UNIT

Die-cast aluminum housing (white finish std)

Universal edge-lit panel (single, double, chevrons)

Universal mounting: surface, recessed, end

Custom wording available

Nickel-cadmium battery



## VANDAL RESISTANT EXIT UNIT

Durable 16 gauge steel housing & faceplate

Polycarbonate shield between frame & faceplate

Tamper resistant screws standard

Full length canopy for ceiling or end mounting

AC only, AC/DC & self-powered operation versions







**BEGHELLI USA**  
3810 Executive Way  
Miramar, FL 33025  
954.442.6600

[www.beghelliusa.com](http://www.beghelliusa.com)