



ACCIAIO COMPARISON

■ ■ ■ BX910, 960, 965, 910 SE

ACCIAIO FAMILY	BX910	BX960	BX965	BX910 SE
Certifications	IP66, IK09, NEMA 4X, BAA, Title 20/24, DLC PREMIUM, UL	IP66, IK10, Title 20/24, DLC PREMIUM, UL	IP67, IK10, Title 20/24, DLC PREMIUM, UL	IP66, IK09, NEMA 4X, BAA, Title 20. UL
Length	2 ft & 4 ft	4 ft	4 ft	2 ft
Operation HT (AC only), SA (AC & EM), SE (EM only)	HT, SA	HT, SA	HT, SA	SE
Housing Construction	24 ga steel	Extruded aluminum	Extruded aluminum	24ga steel
End Caps	Die-cast aluminum	Die-cast aluminum	Die-cast aluminum	Die-cast aluminum
Diffuser	4mm (polycarb)	4mm (polycarb)	4mm (polycarb)	4mm (polycarb)
Finish	Polyester powder coat in gray or white	Clear anodized	Clear anodized	Polyester powder coat in gray or white
Emergency Backup (Integral, 90 min duration, T20 CEC compliant)	1417 lumens (10W)	1500 lumens (10W)	1340 lumens (10W)	1729 lumens (10W)
Wattage	20W, 30W, 50W, 60W	50W, 80W	30W, 50W	10W
Lumens	2585 - 8773	6990 - 11,165	3746 - 6712	1729
Color Temperature	3000K, 4000K, 5000K	3000K, 4000K, 5000K	3000K, 4000K, 5000K	4000K
Input voltage	120 - 277V 347-480V	120 - 277V 347 - 480V	120 - 277V 347 - 480V	120 - 277V
Sensors	Yes	Yes	Yes	No