

CASTEX COMPARISON

CASTEX PORTFOLIO	CAS100	CAS150	CAS300	CAS310	CAS320	CAS350	CAS400	CAS510	CAS600
OPERATION	HT (AC Only)	HT (AC Only)	HT (AC Only)	HT (AC Only)	HT (AC Only)	HT (AC Only)	HT (AC Only)	HT (AC Only)	HT (AC Only)
CLASSIFICATIONS									
Class I Division 1 Groups C & D		•		•	•				•
Class I Division 2 Groups A,B,C,D	•	•	•	•	•	•	•	•	•
Class II Division 1 Groups E,F,G	•	•	•	•	•	•	•	•	•
Class II Division 2 Groups F & G	•	•	•	•	•	•	•	•	•
Class III	•	•	•	•	•	•	•	•	•
HOUSING	Die-cast copper-free aluminum	Die-cast copper-free aluminum	A383 aluminum alloy	A383 aluminum alloy	A383 aluminum alloy	Die-cast copper-free aluminum	Stainless steel	Die-cast copper-free aluminum	Die-cast copper-free aluminum
COLOR TEMP	5000K	5000K	5000K	5000K	5000K	5000K	5000K	5000K	5000K
DIFFUSER	6 mm clear tempered glass	N/A	4 mm tempered glass	4 mm tempered glass	4 mm tempered glass	tempered flat glass	Polycarbonate	Polycarbonate	Polycarbonate with tempered glass cover
WATTAGE	20W, 30W	30W, 40W	60W, 100W, 150W, 200W	60W, 80W, 100W, 150W, 250W	60W, 80W, 100W, 150W	30W, 40W, 50W, 60W	30W, 50W	40W, 60W, 80W	40W, 50W, 60W, 80W, 100W
LUMENS	2000-3000 lm	4200-5600 lm	8400-28000 lm	8400-35000 lm	8400-21000 lm	4370-8276 lm	4200-7000 lm	5600-12000 lm	5600-14000 lm
OPERATING TEMP	-40°F - 104°F (-40°C - 40°C)	-40°F - 149°F (-40°C - 65°C)	-40°F - 131°F (-40°C - 55°C)	-40°F - 140°F (-40°C - 60°C)	-40°F - 131°F (-40°C - 55°C)	-40°F - 122°F (-40°C - 50°C)	-40°F - 140°F (-40°C - 60°C)	-40°F - 140°F (-40°C - 60°C)	-40°F - 140°F (-40°C - 60°C)
MOUNTING	Surface	Surface Pendant	Surface Pendant Hook	Surface Pendant Hook	Surface Pendant	Surface	Surface Cable Pole	Surface	Surface Pendant Chain