

Project: _____

Type: _____

Model: _____

Date: _____



■ specifications: internal

The DLX100 is 100% reliable, there are no internal parts to fail. It is a non-toxic, non-radioactive low profile exit solution. The DLX100 is visible at up to 100 feet.

■ specifications: external

Construction: ABS plastic with photoluminescent panel. The DLX100 can be used for high and/or low level installations and has a 25 year life expectancy. It is visible at 100 feet during a blackout condition. The DLX100 meets current building codes, NFPA Life Safety Code 101 and OSHA requirements; International Building Code 2009/2018; International Fire Code 2009/2018.

■ specifications: electrical

CIRCUIT: Since there is no electricity required, the DLX100 is a safer signage solution, which saves on maintenance and energy costs.

INSTALLATION: Before installation it must be determined that there is a minimum of 5 Fc of LED, Fluorescent, metal halide or mercury vapor light on the face(s) of the sign at all times during building occupancy.

■ specifications: mechanical

The DLX100 series utilizes photoluminescent technology which absorbs and stores ambient light. It is a non-toxic, and non-radioactive low profile emergency lighting solution. The DLX100 features field adjustable chevrons and is constructed of ABS plastic with photoluminescent panel. The DLX100 is NON-TOXIC and NON-RADIOACTIVE which eliminates disposal fees.

■ warranty

The DLX100 Series comes with a 10 year factory warranty. Deliberate damage, misuse, improper installation effectively cancel the warranty.

■ dimensions



■ ordering logic

EXAMPLE: DLX100 P2 B UB

Series	Face No.	Frame Color	Mounting
DLX100	P1 (single)	R (red)	UB (universal mounting bracket)
	P2 (double)	G (green)	
		B (black)	