# **XMR WL**









Job Name:	
Model:	
Type:	
Date:	

## specifications: internal

The **XMR WL** is configured with a 120/277VAC input. Standard features include solid-state charging circuitry, low voltage disconnect, AC lockout and brownout protection. Maintenance free 6V 4.5Ah sealed lead calcium battery.

### specifications: external

The **XMR WL** is constructed from high quality 5VA flame & corrosion resistant, high-impact thermoplastic. Standard gray finish, black is optional. The universal mounting bracket is easily snapped onto the **XMR WL** housing.

#### emergency heads

The **XMR WL** comes with two fully adjustable, ultra-bright, 7W MR-16 LED lamp heads with a fully gasketed enclosure and clear polycarbonate lens cover. The gimbal style head assemblies allow precise positioning. This unit delivers 76' on-center spacing at 7.5' mounting height.


### specifications: electrical

**BATTERY:** The **XMR WL** is configured standard with a single 6V 4.5Ah maintenance free, sealed lead calcium battery. 90 minutes emergency duration minimum. 24 hour charge time. The maximum battery operating temperature is  $+40^{\circ}$ C and the minimum is  $+20^{\circ}$ C without internal heater option (-25°C with the heater option).

**CIRCUIT:** The **XMR WL** features 120/277VAC input with current limit protection. External test switch and monitor LED are standard.

	INPUT WATTS (W)		INPUT AMPS (A)	
	120V	277V	120V	277V
XMR WL	6.0	6.2	0.053	0.025
XMR WL with IH	5.3	6.0	0.050	0.025





Series	Α	В	C
XMR WL	1413/16"	41/4"	5 <sup>5/8</sup> "
	376mm	108mm	143mm

#### certifications

- UL924
- NFPA 101 Life Safety Code
- NEC. OSHA. Local and State Codes
- UL Listed for Wet Locations

#### warranty

The **XMR WL** comes with a 3-year factory warranty. Lamps are not covered under the warranty. Deliberate damage, misuse, or improper installation effectively cancel the warranty.

#### ordering logic

**EXAMPLE: XMR S1WL** 

Series	Capacity	Lamps	Options	
XMR	S1WL (6V 14W)	HO (7W LED lamps)	AT (autotest)	T20 (CEC Title 20 compliant)
			B (black finish)	USA (assembled in USA)
			IH (internal heater)	

